

**DYNAMIC**

**LIGHT  
DUTY**



**18  
MONTH  
WARRANTY**



**Electrical specification**

<b>Voltage:</b>	<b>12V</b>
<b>Capacity C<sup>20</sup>:</b>	<b>80 Ah</b>
<b>Cold cranking current:</b>	<b>760 CCA [SAE]</b>
<b>Reserve Capacity:</b>	<b>138 min</b>

**Mechanical specification**

<b>Dimensional group:</b>	<b>LB4</b>
<b>ETN reference:</b>	<b>668D</b>
<b>Dimensions<sup>A</sup> in mm (LxWxH):</b>	<b>310x175x190</b>
<b>Cell Layout:</b>	<b>2</b>
<b>Terminal Type:</b>	<b>A</b>

**Container**

<b>Case</b>	<b>Material</b>	<b>Polypropylene</b>
	<b>Bottom hold-down</b>	<b>B13/B4</b>
	<b>Colour</b>	<b>Black</b>

<b>Lid</b>	<b>Material</b>	<b>Polypropylene</b>
	<b>Cover design</b>	<b>SMF</b>
	<b>Colour</b>	<b>Black</b>

<b>Vent caps</b>	<b>Material</b>	<b>Polypropylene</b>
	<b>Type</b>	<b>SMF</b>
	<b>Colour</b>	<b>Black</b>

<b>Handles</b>	<b>Material</b>	<b>Polypropylene</b>
	<b>Position</b>	<b>Top - on lid</b>
	<b>Colour</b>	<b>Black</b>


**Battery classification**

<b>Water consumption</b>	<b>Charge retention</b>	<b>Vibration resistance</b>	<b>Endurance Level</b>
<b>W3</b>	<b>C2</b>	<b>V1</b>	<b>E1</b>


**Weight<sup>B</sup>**

<b>Battery weight in kg:</b>	<b>12.80</b>
<b>Acid weight in kg:</b>	<b>5.85</b>
<b>Total battery weight in kg:</b>	<b>18.65</b>

**Layout**



**Hold-down**



**Separator**

<b>Type</b>	<b>PE</b>
-------------	-----------

**A.** Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.  
**B.** Weight may vary ±5%.